






**IEEE 802.3, ISO/IEC 8802.3 10Base2 and 10Base5**

**Trunk Cables – Thinnet and Thicknet**

De-scription	Part No.	UL NEC / C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/100 ft.	dB/100 m
<b>Thinnet 10Base2 • 20 AWG • Stranded (19x32) 0.9 mm Tinned Copper • Duobond® II • 93 % Tinned Copper Braid</b>																			
<b>Ethernet • Foam HDPE Insulation • Grey PVC Jacket</b>																			
	30V 60°C <b>9907</b>	NEC:	500	152	12.6	5.7	0.94 mm	0.102	2.59	Duobond® II	0.185	4.70	50	80%	25.4	83.3	1	0.4	1.4
	UL AWM Style 1354	CL2, CM	U-1000	U-305	25.1	11.4	20 AWG			+ 93% TC							10	1.3	4.3
		CEC:	1000	305	25.1	11.4	(19x32) TC			19.0 /km***							50	2.9	9.5
		CM	1640	500	41.0	18.6	47.9 /km*										100	4.2	13.8
			2500	762	62.6	28.4	28.9 /km**										200	6.1	20.0
			3280	1000	82.2	37.3										400	8.9	29.2	
																700	12.1	39.7	
																900	13.9	45.6	
																1000	14.8	48.6	
			DEC Part No. 17-01248-00																
			For Plenum version of 9907, see 89907 or 82907.																
<b>Plenum • Ethernet • Foam FEP Insulation • Natural Flamarrest® Jacket</b>																			
	300V 75°C <b>82907</b>	NEC:	† 500	152	12.6	5.7	0.94 mm	0.095	2.41	Duobond® II	0.160	4.06	50	80%	25.4	83.3	1	0.4	1.4
		CL2P	U-1000	U-305	23.1	10.5	20 AWG			+ 93% TC							10	1.3	4.3
		CMP	† 1000	305	24.0	10.9	(19x32) TC			19.0 /km***							50	2.9	9.5
		CEC:	† 2500	762	57.5	26.1	47.9 /km*										100	4.2	13.8
		CMP					28.9 /km**										200	6.1	20.0
																400	9.2	30.2	
																700	12.9	42.3	
																900	15.0	49.2	
																1000	16.0	52.5	
<b>Plenum • Ethernet • Foam FEP Insulation • Grey Fluorocopolymer Jacket</b>																			
	300V 150°C <b>89907</b>	NEC:	† 500	152	12.6	5.7	0.94 mm	0.095	2.41	Duobond® II	0.160	4.06	50	80%	25.4	83.3			
		CL2, CM	† 1000	305	24.0	10.9	20 AWG			+ 93% TC									
		CEC:	† 2500	762	60.2	27.3	(19x32) TC			19.0 /km***									
		CM					47.9 /km*												
							28.9 /km**												
			DEC Part No. 17-01246-00																
			Suitable for outdoor and direct burial applications.																
<b>Thinnet 10Base2 • 12 AWG • Solid 2.05 mm Bare Copper • Duobond® IV Quad Shield</b>																			
<b>Ethernet • Foam Polyethylene Insulation • Yellow PVC Jacket</b>																			
	30V 60°C <b>9880</b>	NEC:	500	152	66.1	30.0	2.05 mm	0.243	6.17	Duobond® IV	0.405	10.29	50	78%	25.9	85.0	1	0.2	0.6
	UL AWM Style 1478	CL2, CM	1000	305	131.2	59.5	12 AWG			Quad Shield							5	0.4	1.2
		CEC:	1640	500	220.2	99.9	Solid BC			5.0 /km***							10	0.5	1.7
		CM					9.66 /km*										50	1.2	3.9
							4.66 /km**										100	1.7	5.6
																200	2.6	8.4	
																400	3.9	12.8	
																700	5.5	18.1	
																900	6.5	21.3	
																1000	6.9	22.6	
			DEC Part No. 17-00451-00 5.0 /km																
			For Plenum version of 9880, see 89880.																
			Ring-band stripes marked every 2.5 meters to aid users in tap placement.																
<b>Plenum • Ethernet • Foam FEP Insulation • Orange Fluorocopolymer Jacket</b>																			
	150°C <b>89880</b>	NEC:	† 1000	305	134.3	60.9	2.05 mm	0.245	6.22	Duobond® IV*	0.375	9.53	50	78%	25.9	85.0	1	0.2	0.6
		CL2P	† 1640	500	225.1	102.1	12 AWG			Quad Shield							5	0.4	1.2
		CMP					Solid BC			5.0 /km***							10	0.5	1.7
		CEC:					9.66 /km*										50	1.1	3.8
		CMP					4.66 /km**										100	1.6	5.4
																200	2.5	8.0	
																400	3.8	12.5	
																700	5.6	18.4	
																900	6.8	22.3	
																1000	7.2	23.6	
			DEC Part No. 17-00324-00																
			Suitable for outdoor and direct burial applications.																
			Ring-band stripes marked every 2.5 meters to aid users in tap placement.																

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance  
 † Spools and/or UnReel® cartons are one piece, but length may vary ±10% from length shown.

Duobond® II and Duobond® IV see technical information page 23.13.

 Not RoHS compliant at time of printing.

### IEEE 802.4, MAP & Mini-MAP, IEEE 802.7

#### Broadband Coaxial Cables

De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m
<b>14 AWG • Solid 1.6 mm Copper-Covered Steel • Duobond® IV Quad Shield</b>																			
<b>Gas-Injected Foam Polyethylene Insulation • Grey PVC Jacket</b>																			
	3094A	NEC:	500	152	31.1	14.1	1.63 mm	0.280	7.11	Duobond® IV	0.407	10.34	75	82%	16.2	53.1	1	0.2	0.5
		CL2R	1000	305	62.2	28.2	14 AWG			Quad Shield							2	0.2	0.6
		CMR	† 2000	610	121.9	55.3	Solid CCS			4.9 /km***							5	0.3	0.9
		CEC:					20.0 /km*			7.9 mm							10	0.4	1.2
		CMG					36.1 /km**										20	0.5	1.8
																	50	0.8	2.7
																	100	1.2	3.8
																	200	1.6	5.3
																	300	2.0	6.6
																	400	2.3	7.6



RG-11/U Type

Tap marks every 2.6 meters to aid users in installation.  
152 m and 305 m exact 1 pc.

Sweep tested 5 MHz to 400 MHz.  
CPE jacket optional.

### IEEE 802.5, ISO/IEC 8802.5

#### IBM Cabling System

#### Types 1A and 1

De- Description	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m
<b>IBM Type 1a • 22 AWG • Solid 0.6 mm Bare Copper • Each Pair Individually Beldfoil® Shielded • 65% Overall Tinned Copper Braid • Rip Cord</b>																			
<b>Flame-Retardant Foam Polyethylene Insulation • Black PVC Jacket</b>																			
	IBM Part No. 9688	NEC:	† 500	152	26.5	12.0	0.64 mm	0.099	2.51	Individual	0.296	7.52	150	–	8.5	27.9	4	0.7	2.2
	4716748	CMG	† 1000	305	50.0	22.7	22 AWG			Beldfoil®	x	x					16	1.3	4.4
	33G2772	CEC:	† 2000	610	102.1	46.3	Solid BC			+ Overall	0.431	10.95					100	3.8	12.3
		CMG	† 3600	1098	190.7	86.5				65% TC Braid							300	6.5	21.4
																	100 ††	4.1	13.4
																	300 ††	7.1	23.3
																	600 ††	10.0	32.9



Rip Cord

2-Pair

Meets IEEE 802.5 and TIA/EIA-568-A specifications, ETL verified. For token ring (4/16 Mbps), FDDI over copper, and video applications.  
IBM qualified type 1A media cable for use in IBM cabling systems. For non-suffix "A" type IBM product, see 1634A below.

#### IBM Type 1 • 22 AWG • Solid 0.6 mm Bare Copper • Each Pair Individually Beldfoil® Shielded • 65% Overall Tinned Copper Braid • Rip Cord

De- Description	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m
<b>IBM Type 1 • 22 AWG • Solid 0.6 mm Bare Copper • Each Pair Individually Beldfoil® Shielded • 65% Overall Tinned Copper Braid • Rip Cord</b>																			
<b>Flame-retardant Foam Polyethylene Insulation • Black PVC Jacket</b>																			
	IBM Part No. 1634A	NEC:	† 1000	305	50.0	22.7	0.64 mm	0.099	2.51	Individual	0.296	7.52	150	–	8.5	27.9	4	0.7	2.2
	4716748	CMG	† 2000	610	102.3	46.4	22 AWG			Beldfoil®	x	x					16	1.3	4.4
		CEC:	† 3600	1098	191.1	86.7	Solid BC			+ Overall	0.431	10.95							
		CMG								65% TC Braid									



Rip Cord

2-Pair

Meets IEEE 802.5 and TIA/EIA-568-A specifications, ETL verified.  
IBM qualified type 1A media cable for use in IBM cabling systems. For token ring (4/16 Mbps), FDDI over copper, and video applications.

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • CCS = Copper-Covered Steel • TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance  
† Spools are one piece, but length may vary ±10% from length shown.  
†† Common mode

Duobond® IV see technical information page 23.13.

Not RoHS compliant at time of printing

Industrial Data Solutions® - Industrial Ethernet Cables

Coaxial Cables



De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m

**Thinnest 10Base2 Ethernet • 20 AWG • Stranded (19x32) 0.9 mm Tinned Copper • Duobond® II • 93% Tinned Copper Braid**

Ethernet • Foam HDPE Insulation • Grey PVC Jacket																				
	30V 60°C	<b>9907</b>	NEC:	500	152	12.6	5.7	0.94 mm	0.102	2.59	Duobond® II	0.185	4.70	50	80%	25.4	83.3	1	0.4	1.4
	UL AWM Style 1354		CL2	U-1000	U-305	25.1	11.4	20 AWG			+ 93% TC							10	1.3	4.3
			CM	1000	305	25.1	11.4	(19x32) TC			Braid							50	2.9	9.5
			CEC:	1640	500	41.0	18.6	47.9 Ω/km*			19.0 Ω/km***							100	4.2	13.8
			CM	3280	1000	82.2	37.3	28.9 Ω/km**										200	6.1	20.0
																	400	8.9	29.2	
																	700	12.1	39.7	
																	900	13.9	45.6	
																	1000	14.8	48.6	

DEC Part No. 17-01248-00

Plenum • Ethernet • Foam FEP Insulation • Grey Fluorocopolymer Jacket																				
	300V 150°C	<b>89907</b>	NEC:	† 500	152	12.6	5.7	0.94 mm	0.095	2.41	Duobond® II	0.160	4.06	50	80%	25.4	83.3	1	0.4	1.4
			CL2P	† 1000	305	24.0	10.9	20 AWG			+ 93% TC							10	1.3	4.3
			CMP	† 2500	762	60.2	27.3	(19x32) TC			Braid							50	2.9	9.5
			CEC:					47.9 Ω/km*			19.0 Ω/km***							100	4.2	13.8
			CMP					28.9 Ω/km**										200	6.1	20.0
																	400	9.2	30.2	
																	700	12.9	42.3	
																	900	15.0	49.2	
																	1000	16.0	52.5	

RG-58/U Type

DEC Part No. 17-01248-00

Suitable for outdoor and direct burial applications.

**Thickest 10Base5 Ethernet • 12 AWG • Solid 2.1 mm Bare Copper • Duobond® IV Quad Shield**

Ethernet • Foam PE Insulation • Yellow PVC Jacket																				
	30V 60°C	<b>9880</b>	NEC:	500	152	66.1	30.0	2.05 mm	0.243	6.17	Duobond® IV	0.405	10.29	50	78%	25.9	85.3	1	0.2	0.6
	UL AWM Style 1478		CL2	1000	305	131.2	59.5	12 AWG			Quad Shield							5	0.4	1.2
			CM	1640	500	220.2	99.9	Solid BC			5.0 Ω/km***							10	0.5	1.7
			CEC:					9.7 Ω/km*										50	1.2	3.9
			CM					4.7 Ω/km**										100	1.7	5.6
																	200	2.6	8.4	
																	400	3.9	12.8	
																	700	5.5	18.1	
																	900	6.5	21.3	
																	1000	6.9	22.6	

DEC Part No. 17-00451-00

Ring-band stripes marked every 2.5 m to aid users in tap placement.

Plenum • Foam FEP Insulation • Orange Fluorocopolymer Jacket																				
	150°C	<b>89880</b>	NEC:	1000	305	134.3	60.9	2.05 mm	0.245	6.22	Duobond® IV	0.375	9.53	50	78%	25.9	85.3			see above
			CL2P	†† 1640	500	225.1	102.1	12 AWG			Quad Shield									
			CMP					Solid BC			5.0 Ω/km***									
			CEC:					9.7 Ω/km*												
			CMP FT6					4.7 Ω/km**												

DEC Part No. 17-00324-00

Ring-band stripes marked every 2.5 m to aid users in tap placement. Suitable for outdoor and direct burial applications.

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance

† Spools are one piece, but length may vary ±10% from length shown.

†† Final put-up length may vary from length shown ±10% for spools and reels, ±5% for UnReel® cartons.

Duobond® II and Duobond® IV see technical information page 23.13.