

## Interconnect Cables

Indoor


De- scription	Part No.	No. of Fibers	Standard Lengths		Standard Unit Weight		Fiber Size μm	Nom. Buffer/ Tube OD		Strength Members	Nominal OD		Central Element mm	Pulling Tension N	Crush Re- sistance kN/m	Energy kJ/m	Bending radii cable (mm)	
			ft.	m	lbs.	kg		inch	mm		inch	mm					static	dyna- mic

**GIOK • Pigtailed • Semi-Tight Buffer • Excellent Strippability • I-K**

<b>Dry Construction • Halogen-Free Jacket</b> (Blue, Green, Green with Black Rings or Yellow)																		
-30/70°C IEC 60332-2			6888	2100	3.1	1.4	Ø 245 ± 10	-			no		3	4	19			



GIOK101	1	62.5/125 OM1 in Blue										0.04	0.9	25	35
GIOK201	1	50/125 OM2 in Green										0.04	0.9	25	35
GIOK301	1	50/125 OM3 in Green with Black rings										0.04	0.9	25	35
GIOK401	1	50/125 OM2e in Green										0.04	0.9	25	35
GIOK901	1	9/125 OS1 in Yellow										0.04	0.9	25	35




Strippability secondary coating = 100 cm

**GIPS • Simplex • Semi-Tight Buffer • Excellent Strippability • I-W(ZN)H**

<b>Jelly-Filled Construction • Orange FRNC/LSNH Jacket</b>																		
-5/55°C IEC 60332-1			6888	2100	32.9	14.9	Ø 245 ± 10	Reinforced Aramid Yarn			no		200	10	128			



GIPSxA1												0.06	1.6	24	32
GIPSxB1												0.07	1.8	27	36
GIPSxC1												0.08	2.0	30	40
GIPSxD1												0.09	2.4	36	48
GIPSxE1												0.11	2.8	42	56
GIPSxF1												0.12	3.0	45	60



Strippability secondary coating = 100 cm  
 Color Code: see chart page 16.23

Optical characteristics see page 16.21.