

## Security and Alarm Cables

Commercial Applications Unshielded




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

**22 AWG • Stranded (7x30) 0.8 mm Bare Copper • Numbered and Color Coded • Rip Cord**

**Polyethylene Insulation • Grey FRNC/LSNH Jacket**

300V 70°C	IEC 60754-2		0.76 mm 22 AWG (7x30) BC	0.049	1.25	Unshielded	see chart below
--------------	-------------	--	--------------------------------	-------	------	------------	-----------------



Part No.	Conductor	Length (ft.)	Length (m)	Weight (lbs.)	Weight (kg)	Insulation OD (inch)	Insulation OD (mm)
<b>4500UE</b>	2 CDR	328 1640	100 500	3.1 15.4	1.4 7.0	0.130	3.30
<b>4501UE</b>	3 CDR	328 1640	100 500	3.1 15.4	1.4 7.0	0.130	3.30
<b>4502UE</b>	4 CDR	328 1640	100 500	5.3 26.0	2.4 11.8	0.154	3.90
<b>4504UE</b>	6 CDR	328 1640	100 500	7.3 36.2	3.3 16.4	0.177	4.50
<b>4506UE</b>	8 CDR	328 1640	100 500	8.8 43.7	4.0 19.8	0.193	4.90
<b>4509UE</b>	12 CDR	328 1640	100 500	13.4 66.8	6.1 30.3	0.232	5.90

BC = Bare Copper • DCR = DC resistance

### Color Code

Cond. No.	Color	Cond. No.	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Grey
5	Brown	11	Pink
6	Blue	12	Tan