

Security Composite Cables

CCTV Plus Audio or Pan and Tilt CCTV Control Applications



De-scription	Part No.	UL NEC / C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Shielding Material	Nominal OD		Component	Description	Shielding Material & Nom. DCR	Insulation Material & Colors	Component Jacket Material & Colors	Component OD		
			ft.	m	lbs.	kg		inch	mm						inch	mm	
Composite • (1) Pair Unshielded 18 AWG • (1) Coax Solid 0.8 mm Bare Copper • 95 % Bare Copper Braid																	
PVC Insulation (Pairs) • Foam Insulation (Coax) • Black PVC Jacket																	
300V 75°C	549945	NEC: CM CEC: CM FT1	500 1000	152 305	30.0 60.2	13.6 27.3	Unshielded	0.460	11.68	2xData	1-Pair 18 AWG 1.22 mm (7x26) BC	Unshielded	PVC 1.47 mm	PVC Black	0.228	5.79	
											1xCoax	20 AWG 0.8 mm Solid BC	95% BC	Foam Polyolefin	PVC Black	0.232	5.89
Color Code 1-Pair: Black and Red																	
PVC Insulation (Pairs) • Foam Insulation (Coax) • Grey FRNC/LSNH Jacket																	
300V 70°C	449945	IEC 60754-2	328 1640	100 500	19.8 98.8	9.0 44.8	Unshielded	0.461	11.70	2xData	1-Pair 18 AWG 1.22 mm (7x26) BC	Unshielded	PE 1.47 mm	FRNC Grey	0.228	5.79	
											1xCoax	20 AWG 0.8 mm Solid BC	95% BC	Foam PE	FRNC Grey	0.232	5.90
Color Code 1-Pair: Black and Red																	
Composite • (1) Pair Unshielded 18 AWG • (1) Coax Solid 1.0 mm Bare Copper • 95 % Bare Copper Braid																	
PVC Insulation (Pairs) • Foam Insulation (Coax) • Black PVC Jacket																	
300V 75°C	539945	NEC: CM CEC: CM FT1	500 1000	152 305	34.2 69.0	15.5 31.3	Unshielded	0.500	12.70	2xData	1-Pair 18 AWG 1.22 mm (7x26) BC	Unshielded	PVC 1.47 mm	PVC Black	0.228	5.79	
											1xCoax	18 AWG 1.0 mm Solid BC	95% BC	Foam Polyolefin	PVC Black	0.266	6.76
Color Code 1-Pair: Black and Red																	
PVC Insulation (Pairs) • Foam Insulation (Coax) • Grey FRNC/LSNH Jacket																	
300V 70°C	439945	IEC 60754-2	328 1640	100 500	22.9 114.9	10.4 52.1	Unshielded	0.500	12.70	2xData	1-Pair 18 AWG 1.22 mm (7x26) BC	Unshielded	PE 1.47 mm	FRNC Grey	0.228	5.79	
											1xCoax	18 AWG 1.0 mm Solid BC	95% BC	Foam PE	FRNC Grey	0.268	6.80
Color Code 1-Pair: Black and Red																	





BC = Bare Copper • DCR = DC resistance

20 • New Generation® Cables

Security Composite Cables

CCTV Plus Audio or Pan and Tilt CCTV Control Applications



De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Shielding Material	Nominal OD		Compo- nent	Description	Shielding Material & Nom. DCR	Insulation Material & Colors	Component Jacket Material & Colors	Component Insulation OD	
			ft.	m	lbs.	kg		inch	mm						inch	mm
Composite • (2) Conductor 26 AWG • (1) Coax Solid 0.4 mm Bare Copper • Alu Triplex/Duplex • 72% Tinned Copper Braid																
PVC Insulation (Conductors) • Gas-Injected PE Insulation (Coax) • Grey PVC Jacket																
	SEC0001		328	100	11.7	5.3	Unshielded	0.252	6.40	1xData	2 Conductor 26 AWG 0.50 mm (16x0.193) BC	Unshielded	PVC 1.90 mm	PVC	0.062	1.57
										1xCoax	21 AWG 0.41 mm Solid BC	Alu Triplex/Duplex 72% TC Braid	Foam Polyethylene	PVC	0.142	3.60
Composite • (2) Conductor 16 AWG • (1) Coax Solid 0.8 mm BC • Alu Triplex/Duplex • 55% Tinned Copper Braid • (2) Conductor 26 AWG																
PVC Insulation (Conductors) • Gas-Injected PE Insulation (Coax) • Grey PVC Jacket																
	SEC0002		328	100	29.8	13.5	Unshielded	0.315	8.00	1xData	2 Conductor 16 AWG 1.50 mm (30x0.25) BC	Unshielded	PE 3.50 mm	PVC	0.101	2.56
										1xCoax	20 AWG 0.81 mm Solid BC	Alu Triplex/Duplex 55% TC Braid	Foam Polyethylene	PVC	0.142	3.60
										1xControl	2 Conductor 26 AWG 0.50 mm (16x0.20) BC	Unshielded	PE 3.50 mm	PVC	0.062	1.57
Composite • (2) Conductor 20 AWG • (1) Coax Solid 0.4 mm Bare Copper • Alu Triplex/Duplex • 72% Tinned Copper Braid																
PVC Insulation (Conductors) • Gas-Injected PE Insulation (Coax) • Grey PVC Jacket																
	SEC0003		328	100	14.8	6.7	Unshielded	0.291	7.40	1xData	2 Conductor 20 AWG 1.00 mm (32x0.20) BC	Unshielded	PVC 1.90 mm	PVC	0.085	2.17
										1xCoax	26 AWG 0.41 mm Solid BC	Alu Triplex/Duplex 72% TC Braid	Foam Polyethylene	PVC	0.142	3.60
Composite • (2) Conductor 24 AWG • (1) Coax Solid 0.4 mm BC • Alu Triplex/Duplex • 72% Tinned Copper Braid • (2) Conductor 26 AWG																
PVC Insulation (Conductors) • Gas-Injected PE Insulation (Coax) • Grey PVC Jacket																
	SEC0004		328	100	13.4	6.1	Unshielded	0.260	6.60	1xData	2 Conductor 24 AWG 0.22 mm (30x0.25) BC	Unshielded	PVC 1.90 mm	PVC	0.045	1.15
										1xCoax	26 AWG 0.41 mm Solid BC	Alu Triplex/Duplex 72% TC Braid	Foam Polyethylene	PVC	0.142	3.60
										1xControl	2 Conductor 26 AWG 0.50 mm (16x0.20) BC	Unshielded	PE 3.50 mm	PVC	0.062	1.57

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance