

Fire Alarm Cables
Commercial Applications
Power-Limited Unshielded




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

16 AWG • Solid 1.3 mm Bare Copper • Numbered and Color Coded • Rip Cord

PVC Insulation • Red PVC Jacket

300V
75°C
NEC:
FPLR
CEC:
CMG FT4
1.29 mm
16 AWG
Solid BC
0.061 1.54 Unshielded




Rip Cord

5220UL	2 CDR	500	152	13.0	5.9	0.174	4.42	Black, Red
		U-1000 1000	U-305 305	24.0 25.1	10.9 11.4			

5222UL	4 CDR	1000	305	45.0	20.4	0.204	5.18	Black, Red, Brown, Blue
---------------	-------	------	-----	------	------	-------	------	-------------------------

Polyethylene Insulation • Red FRNC / LSNH Jacket

300V
70°C
IEC 60754-2
1.29 mm
16 AWG
Solid BC
0.077 1.95 Unshielded



Rip Cord


4220UL	2 CDR	328	100	7.7	3.5	0.173	4.40	Black, Red
		1640	500	38.4	17.4			

4222UL	4 CDR	1640	500	67.7	30.7	0.201	5.10	Black, Red, Brown, Blue
---------------	-------	------	-----	------	------	-------	------	-------------------------

14 AWG • Solid 1.6 mm Bare Copper • Numbered and Color Coded • Rip Cord

PVC Insulation • Red PVC Jacket

300V
75°C
NEC:
FPLR
CEC:
CMG FT4
1.63 mm
14 AWG
Solid BC
0.077 1.96 Unshielded



Rip Cord

5120UL	2 CDR	500	152	19.0	8.6	0.213	5.41	Black, Red
		1000	305	38.1	17.3			

5122UL	4 CDR	1000	305	70.1	31.8	0.251	6.38	Black, Red, Brown, Blue
---------------	-------	------	-----	------	------	-------	------	-------------------------

Polyethylene Insulation • Red FRNC / LSNH Jacket

300V
70°C
IEC 60754-2
1.63 mm
14 AWG
Solid BC
0.085 2.15 Unshielded



Rip Cord

4120UL	2 CDR	328	100	11.2	5.1	0.213	5.40	Black, Red
		1640	500	56.0	25.4			

4122UL	4 CDR	328	100	19.8	9.0	0.252	6.40	Black, Red, Brown, Blue
		1640	500	99.9	45.3			

BC = Bare Copper • DCR = DC resistance