


**CSA Control Cable**

## 600V CIC Multi-conductor Cables

Description	Part Number	No. of Cond.	Cable Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm

**8 AWG** Stranded (7x16) Bare Copper Conductors**Cross-linked Polyethylene Insulation • Black PVC Jacket** (Color Code: Black and Numbered)

CSA C22.2#131, Type CIC	<b>22160</b>	2	240	357	.045	1.14	.060	1.52	.863	21.92
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	<b>22161</b>	3	308	458	.045	1.14	.060	1.52	.898	22.81
	<b>22162</b>	4	379	564	.045	1.14	.060	1.52	.957	24.31




Rip Cord

-25°C Installed  
-40°C to +90°C (Dry) (75°C Wet)

**6 AWG** Stranded (7x14) Bare Copper Conductors**Cross-linked Polyethylene Insulation • Black PVC Jacket** (Color Code: Black and Numbered)

CSA C22.2#131, Type CIC	<b>22170</b>	2	279	415	.060	1.52	.060	1.52	.711	18.06
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	<b>22171</b>	3	383	570	.060	1.52	.060	1.52	.756	19.20




Rip Cord

-25°C Installed  
-40°C to +90°C (Dry) (75°C Wet)

**4 AWG** Stranded (7x12) Bare Copper Conductors**Cross-linked Polyethylene Insulation • Black PVC Jacket** (Color Code: Black and Numbered)

CSA C22.2#131, Type CIC	<b>22180</b>	2	390	580	.060	1.52	.060	1.52	.800	20.32
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	<b>22181</b>	3	580	863	.060	1.52	.080	2.03	.891	22.63



Rip Cord

-25°C Installed  
-40°C to +90°C (Dry) (75°C Wet)