


CSA Control Cable

1000V Teck90 Cables

Description	Part No.	No. of Cond.	Cable Weight		Inner Jacket OD		Armor OD		Outer Jacket		Maximum Pull Tension		Minimum Bend Radius	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm	Lbs.	N	Inch	mm

14 AWG Stranded (7x22) Bare Copper Conductors • 14 AWG Bare Copper Ground Wire**Aluminum Interlocked Armor • .045" (1.14mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket**


CSA C22.2#131	C5701	3	251	374	.47	11.94	.67	17.02	.73	18.54	162	721	9.2	233.68
FT4 Flame Test	C5702	4	301	448	.51	12.95	.71	18.03	.81	20.57	216	961	9.7	246.38



Rip Cord

HAZ LOC
CSA C22.2#0.3 Clause 4.31 Low Acid Gas**12 AWG Stranded (7x20) Bare Copper Conductors • 14 AWG Bare Copper Ground Wire****Aluminum Interlocked Armor • .045" (1.14mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket**


CSA C22.2#131	C5730	2	253	377	.48	12.19	.68	17.27	.74	18.80	172	765	9.3	236.22
FT4 Flame Test	C5731	3	291	433	.51	12.95	.71	18.03	.76	19.30	258	1148	9.7	246.38
	C5732	4	368	548	.59	14.99	.75	19.05	.85	21.59	344	1531	10.8	274.32



Rip Cord

HAZ LOC
CSA C22.2#0.3 Clause 4.31 Low Acid Gas**10 AWG Stranded (7x18) Bare Copper Conductors • 12 AWG Bare Copper Ground Wire****Aluminum Interlocked Armor • .045" (1.14mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket**


CSA C22.2#131	C5760	2	285	424	.56	14.22	.79	19.99	.70	17.71	296	1317	10.3	261.62
FT4 Flame Test	C5761	3	389	581	.59	14.99	.79	20.07	.85	21.59	444	1976	10.3	261.62
	C5762	4	460	687	.65	16.51	.85	21.59	.90	22.86	592	2634	11.5	292.10



Rip Cord

HAZ LOC
CSA C22.2#0.3 Clause 4.31 Low Acid Gas**8 AWG Stranded (7x16) Bare Copper Conductors • 10 AWG Bare Copper Ground Wire****Aluminum Interlocked Armor • .045" (1.14mm) XLPE Insulation • PVC Inner Jacket • Black PVC Outer Jacket**

CSA C22.2#131	C5583	2	407	607	.59	14.99	.78	19.81	.86	21.84	384	1709	10.6	269.24
FT4 Flame Test	C5581	3	471	703	.63	16.00	.83	21.08	.90	22.86	576	2563	10.8	274.32
	C5582	4	606	905	.69	17.53	.89	22.61	.97	24.64	768	3418	12.5	317.50



Rip Cord

Dual Rated 600V, 1000V
HAZ LOC
CSA C22.2#0.3 Clause 4.31 Low Acid Gas

XLPE = Cross-linked Polyethylene

Color Code: 2 conductors — Black, White (If required, a Red conductor can be used in place of White.)
 3 conductors — Black, Red, Blue (If required, a White conductor can be used in place of Blue.)
 4 conductors — Black, Red, Blue, White
 5 or more conductors — Black and numbered