

# Line Level Analog Audio Cable

## Single- and Double-Pair Cables



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance				
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m	
<b>22 AWG Stranded (19x34) TC Conductors • Dual Twisted Pairs • Overall Beldfoil® Shield (100% Coverage) • 24 AWG Stranded TC Drain Wire</b> <b>PVC Insulation • PVC Jacket in Zip-Cord Construction (Red &amp; Green, Red &amp; Black, Red &amp; Purple or Red &amp; Gray)</b>																			
150V RMS 60°C	<b>1504A</b>	NEC: CM CEC: CM	2	Black, Red	U-1000 2000 ▲	U-304.8 609.8	32.0 64.0	14.5 29.0	.010 .25	.020 .51	.143 .286	3.63 7.26	57 187	100 328					

\*2000 ft. put-up available in Red & Gray or Red & Green only.  
The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.

<b>22 AWG Stranded (7x30) TC Conductors • Dual Twisted Pairs • Overall Beldfoil Shield (100% Coverage) • 22 AWG Stranded TC Drain Wire</b> <b>Polyolefin Insulation • PVC Jacket in Zip-Cord Construction (Red &amp; Green, Red &amp; Gray, Red &amp; Black or Red &amp; Purple)</b>																			
300V RMS 105°C	<b>9451D</b>	NEC: CMR CEC: CMG FT4	2	Black, Red	U-1000 2000 *	U-304.8 620.8	29.0 62.0	13.2 28.1	.008 .20	.020 .51	.135 .270	3.43 6.86	34 112	67 220					

\*2000 ft. put-up available in Red & Green only.  
The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.

<b>Plenum • FEP Insulation • White Flamarrest® Jacket in Zip-Cord Construction</b>																			
300V RMS 60°C	<b>9451DP</b> <small>new</small>	NEC: CMP CEC: CMP FT6	2	Black & Red, Black & White	1000	304.8	24.0	10.9	.007 .18	.017 .43	.127 .269	3.23 6.83	35 115	67 220					

The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.

<b>20 AWG Stranded (7x28) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 20 AWG Stranded TC Drain Wire</b> <b>PVC Insulation • Beige PVC Jacket</b>																			
UL AWM Style 2464 (300V RMS 80°C)	<b>9154</b>	NEC: CMG CEC: CMG FT4	1	Black, Red	U-500 500 U-1000 1000	U-152.4 152.4 U-304.8 304.8	11.5 12.0 22.0 23.0	5.2 5.5 10.0 10.5	.014 .36	.031 .79	.198 5.03	60 197	100 328						

9154 has 22 AWG stranded tinned copper drain wire.

<b>Polyethylene Insulation • Chrome PVC Jacket</b>																			
UL AWM Style 2092 (300V RMS 60°C)	<b>8762</b>	NEC: CM CEC: CM	1	Black, Clear	100 250 U-500 500 U-1000 1000 2000 10000	30.5 76.2 U-152.4 152.4 U-304.8 304.8 609.6 3048.0	3.2 6.3 12.0 12.0 23.0 23.0 46.0 240.0	1.5 2.8 5.5 5.5 10.5 10.5 20.9 109.1	.016 .41	.028 .71	.204 5.18	27 89	49 161						

UL AWM Style 2092 (300V RMS 60°C)	<b>9464</b>	NEC: CM CEC: CM	1	Black, Clear	U-500 U-1000	U-152.4 U-304.8	17.0 32.0	7.7 14.5	.016 .41	.035 .89	.214 5.44	27 89	49 161						
--------------------------------------	-------------	--------------------------	---	-----------------	-----------------	--------------------	--------------	-------------	-------------	-------------	--------------	----------	-----------	--	--	--	--	--	--

The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is on the inside of foil shield.

<b>20 AWG Stranded (7x28) Tinned Copper Conductors • Twisted Pair • Tinned Copper Spiral Wrapped Shield (89% Coverage)</b> <b>PVC Insulation • Chrome PVC Jacket</b>																			
UL AWM Style 2095 (300V RMS 80°C)	<b>8759</b>	NEC: CMG CEC: CMG FT4	1	Black, Red	U-500 U-1000 1000	U-152.4 U-304.8 304.8	12.5 24.0 25.0	5.7 10.9 11.4	.016 .41	.025 .64	.199 5.05	47 154	79 259						

FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

\* Capacitance between conductors.

\*\* Capacitance between one conductor and other conductors connected to shield.

# BELDEN

For more information, contact [Belden Technical Support: 1-800-BELDEN-1](mailto:TechnicalSupport@belden.com) • [www.belden.com](http://www.belden.com)

[Belden114@cablcon.kr](mailto:Belden114@cablcon.kr) / 0707-434-7704 / Fax. 02-744-0909 / [www.CableCon.co.kr](http://www.CableCon.co.kr)