

Analog Multi-Quad Snake Cable

Super-Flexible, High-Performance Cables
 Individually Shielded and Jacketed Quads



Individually Shielded and Jacketed Quads

Not NEC Rated

Product Description

26 AWG* stranded (19x38) bare copper conductor. Polyethylene insulation. Quads individually shielded with bare copper "French Braid," each quad with 26 AWG tinned copper drain wire. Color-coded PVC inner jackets (see table below) with overall Matte Black PVC jacket and 20 AWG tinned copper drain wire.


Color Code: Blue, White, Blue w/White stripe, White w/Blue stripe.

Specifications

Nominal OD — Conductor	.020" (.51mm)
Nominal OD — Insulation	.045" (1.14mm)
Inner Quad Jacket OD	.157" (3.99mm)
Nominal DCR	
Conductor	36.0 Ω/M' (11.8 Ω/km)
Shield (Inner Pair)	6.8 Ω/M' (2.23 Ω/km)
Voltage Rating	100V RMS
Temperature Rating	60°C
Nominal Impedance	40Ω
Nominal Velocity of Propagation	66%
Nominal Capacitance	
Between Conductors and Shield	39 pF/Ft. (129 pF/m)
Between Conductors in Quad Config.	57 pF/Ft. (188 pF/m)

DCR = DC Resistance

*22 AWG equivalent DCR when connected to a 3-pin XLR



Part No.	No. of Quads	Standard Lengths		Standard Unit Weight		Nominal OD	
		Ft.	m	Lbs.	kg	Inch	mm

Super-Flexible Quads

26 AWG							
7884A	2	250	76.2	27.0	12.3	.458	11.63
		500 †	152.4	49.0	22.2		
		1000 †	304.8	98.0	44.4		
7885A	4	250	76.2	36.3	16.4	.498	12.65
		500 †	152.4	70.0	31.8		
		1000 †	304.8	136.0	61.7		
7886A	8	500 †	152.4	146.5	66.6	.782	19.86
		1000 †	304.8	314.0	142.4		
7887A	12	250	76.2	89.5	40.6	.828	21.03
		500 †	152.4	177.5	80.5		
		1000 †	304.8	365.0	165.6		
7888A	16	250	76.2	114.0	51.7	.938	23.83
		500 †	152.4	238.5	108.2		
		1000 †	304.8	468.0	212.3		
7889A	24	500 †	152.4	396.0	180.0	1.232	31.29
		1000 †	304.8	798.0	362.0		

†Length may vary -10% to +0% from length shown.

Inner Jacket Colors:

Quad No.	Jacket Color	Quad No.	Jacket Color
1	Brown	8	Gray
2	Red	9	White
3	Orange	10	Black
4	Yellow	11	Beige
5	Green	12	Pink
6	Blue	13-24	Gray (numbered)
7	Purple		



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

Belden114@cablecon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr