

AES/EBU Digital Audio CableMulti-Pair Snake Cables
Individually Shielded Pairs**Individually Shielded Pairs**

NEC: CM (CEC: CM)

Product Description

24 AWG stranded (7x32) tinned copper conductors. Datalene® insulation. Twisted pairs individually Beldfoil® shielded (100% Coverage). Overall Chrome PVC jacket and 24 AWG stranded tinned copper drain wire.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.


Color Code: See Chart 3 (in Technical Information Section)

Specifications

Nominal OD — Conductor	.024" (.60mm)
Nominal OD — Insulation	.061" (1.55mm)
Approvals	
NEC	CM
CEC	CM
UL Ratings	UL AWM Style 2493
Voltage Rating	300V
Temperature Rating	60°C
Non UL Temperature Rating	80°C
Nominal DCR	
Conductor	24.0Ω/M' (78.7Ω/km)
Shield	15.0Ω/M' (49.2Ω/km)
Nominal Impedance	100Ω
Nominal Velocity of Propagation	76%
Nominal Capacitance	
Between Conductors	12.5 pF/Ft. (41.0 pF/m)
Between Conductor/Shield*	23.2 pF/Ft. (76.1 pF/m)

DCR = DC Resistance

*Capacitance between one conductor and other conductors connected to shield.



Z-Fold®

Part No.	No. of Pairs	Standard Lengths		Standard Unit Weight		Nominal OD	
		Ft.	m	Lbs.	kg	Inch	mm

Individually Shielded Pairs NEC: CM (CEC: CM)

24 AWG							
9729	2	100	30.5	4.3	2.0	.266	6.76
		500	152.4	20.5	9.3		
		1000	304.8	39.0	17.7		
		10000 [†]	3048.0	390.0	176.9		

For Plenum version of 9729, see 89729 or 82729.

9730	3	100	30.5	5.1	2.3	.334	8.48
		500	152.4	24.5	11.1		
		1000	304.8	46.0	20.9		
		10000 ^{††}	3048.0	520.0	236.4		

For Plenum version of 9730, see 89730.

9728	4	100	30.5	6.0	2.7	.363	9.22
		500	152.4	29.0	13.2		
		1000	304.8	51.0	23.1		

For Plenum version of 9728, see 89728.

9731	6	100	30.5	7.4	3.4	.421	10.69
		500	152.4	42.0	19.1		
		1000	304.8	83.0	37.7		

For Plenum version of 9731, see 89731.

9732	9	100	30.5	9.9	4.5	.488	12.40
		500	152.4	57.0	25.8		
		1000	304.8	106.0	48.1		

For Plenum version of 9732, see 89732.

9733	11	500	152.4	75.0	34.1	.575	14.61
------	----	-----	-------	------	------	------	-------

9734	12	500	152.4	79.5	36.1	.575	14.61
		1000	304.8	154.0	70.0		

For Plenum version of 9734, see 89734.

9735	15	500	152.4	95.0	43.2	.639	16.23
		1000	304.8	185.0	84.1		

9736	17	500	152.4	103.5	47.0	.671	17.04
		1000	304.8	210.0	95.5		

9737	19	1000	304.8	231.0	105.0	.671	17.04
------	----	------	-------	-------	-------	------	-------

9738	27	1000	304.8	334.0	151.8	.797	20.24
------	----	------	-------	-------	-------	------	-------

[†] Total length may vary -10 to +5% from length shown and may contain 2 pieces. Minimum length of any one piece will be 1500 ft.

^{††} Total length may vary -10 to +20% from length shown and may contain 2 pieces. Minimum length of any one piece will be 1500 ft.