

AES/EBU Digital Audio Cable

Plenum-Rated, Multi-Pair Snake Cables
Individually Shielded Pairs

**Individually Shielded Pairs**

NEC: CMP (CEC: CMP FT6)

Product Description

24 AWG stranded (7x32) tinned copper conductors. Foam FEP insulation. Twisted pairs individually Beldfoil® shielded (100% Coverage). Overall Gray fluorocopolymer jacket (except 82729 which has Natural Flamarrest® jacket). 24 AWG stranded tinned copper drain wire.

Color Code: See Chart 5 (in Technical Information Section)

Specifications

Nominal OD — Conductor .024" (.60mm)

Nominal OD — Insulation .062" (1.57mm)

Approvals

NEC CMP
CEC CMP FT6

UL Ratings Non-conduit

Voltage Rating 300V RMS

Nominal DCR

Conductor 23.3Ω/M' (76.4Ω/km)
Shield 14.4Ω/M' (47.2Ω/km)

Nominal Impedance 100Ω


Nominal Velocity of Propagation 76%

Nominal Capacitance

Between Conductors 13.5 pF/Ft. (44 pF/m)
Between Conductor/Shield* 22.5 pF/Ft. (73.8 pF/m)

DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene

*Capacitance between one conductor and other conductors connected to shield.



Part No.	No. of Pairs	Standard Lengths		Standard Unit Weight		Nominal OD	
		Ft.	m	Lbs.	kg	Inch	mm

Plenum Individually Shielded NEC: CMP (CEC: CMP FT6)

24 AWG							
82729	2	U-1000 1000	U-304.8 304.8	26.0 28.0	11.8 12.7	.255	6.48
89729	2	500 1000	152.4 304.8	17.0 31.0	7.7 14.1	.261	6.63
89730	3	500 1000	152.4 304.8	21.5 40.0	9.8 18.2	.278	7.06
89728	4	500 1000	152.4 304.8	26.5 50.0	12.0 22.7	.307	7.80
89705	5	500 1000	152.4 304.8	30.5 62.0	13.9 28.2	.333	8.46
89731	6	500 1000	152.4 304.8	35.0 71.0	15.9 32.3	.361	9.17
89757	7	500 1000	152.4 304.8	39.5 80.0	18.0 36.4	.361	9.17
89732	9	1000	304.8	108.0	49.0	.433	10.99
89734	12	500 1000	152.4 304.8	71.0 140.0	32.3 63.6	.498	12.65
89758	18	500 1000	152.4 304.8	100.5 204.0	45.7 92.7	.616	15.65

Spools are one piece, but length may vary ±10% from length shown.
Unreel® carton may vary -5% to +10% from length shown.