


Microphone and Musical Instrument Cable

Two-Conductor, Low-Impedance Cables


High-Conductivity Copper




Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance							
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m				
24 AWG Stranded (19x36) HC TC Conductors • Twisted Pair • Noise Reducing Tape • Beldfoil® Shield (100% Coverage) • TC Drain Wire																						
High-density Polyethylene Insulation • Black PVC Jacket																						
 200V RMS 75°C	9452	—	2	Black, Red	U-500	U-152.4	6.5	3.0	.008	.20	.020	.51	.135	3.43	30	98	58	190				
					500	152.4	6.0	2.7														
					U-1000	U-304.8	12.0	5.5														
					1000	304.8	12.0	5.5														

Shorting Fold


24 AWG Stranded (27x38) High-conductivity Bare Copper Conductors • Bare Copper Spiral Shield (92% Coverage)**PVC Insulation • Black Matte PVC Jacket**

 100V RMS 60°C	1813A	—	2	Red, Blue	328	100.0	10.2	4.6	.017	.43	.055	1.40	.236	5.99	33	108	61	200
					1000	304.8	31.0	14.1										

22 AWG Stranded (16x34) High-conductivity Tinned Copper Conductors • Cotton Braid • Double TC Braid Shield (85% Coverage)**Polyethylene Insulation • Chrome PVC Jacket**

 1000V RMS 80°C	8422	—	2	Clear, Black	500	152.4	15.0	6.8	.021	.53	.022	.56	.231	5.87	18	59	32	105			
					U-1000	U-304.8	31.0	14.1													
					1000	304.8	33.0	15.0													

20 AWG Stranded (26x34) High-conductivity TC Conductors • Rayon Braid • TC Braid Shield (85% Coverage) • Cotton Wrap**EPDM Rubber Insulation • EPDM Jacket (Available in Black, Red, Yellow or Blue)***


 600V RMS 90°C	8412	—	2	White, Black	100	30.5	5.2	2.4	.023	.58	.035	.89	.262	6.65	30	98	55	180				
					250	76.2	12.0	5.5														
					U-500	U-152.4	24.0	10.9														
					500	152.4	22.0	10.0														
					U-1000	U-304.8	46.0	20.9														

*Red, Yellow or Blue available in 1000 ft. put-up only.


EPDM Rubber Insulation • Brown Hypalon® Jacket

 600V RMS 60°C VW-1	8402	—	2	White, Black	500	152.4	25.0	11.3	.023	.58	.035	.89	.263	6.68	30	98	55	180
					U-1000	U-304.8	52.0	23.6										

18 AWG Stranded (41x34) High-conductivity TC Conductors • Rayon Braid • TC Braid Shield (85% Coverage) • Cotton Wrap**EPDM Rubber Insulation • Black Neoprene Jacket**

 600V RMS 60°C	8428	—	2	White, Black	100	30.5	6.3	2.8	.023	.58	.030	.76	.290	7.37	35	115	60	197				
					U-500	U-152.4	29.0	13.2														
					500	152.4	28.0	12.7														
					1000	304.8	59.0	26.8														

16 AWG Stranded (65x34) High-conductivity TC Conductors • Rayon Braid • Paper Wrap • TC Braid Shield (85% Coverage) • Cotton Wrap**EPDM Rubber Insulation • Brown Hypalon® Heavy-duty Jacket**

 600V RMS 60°C VW-1	8408	—	2	Black, White	500	152.4	50.0	22.7	.037	.94	.040	1.02	.380	9.65	30	98	55	180

BC = Bare Copper • EPDM = Ethylene Propylene Diene Monomer • HC = High-conductivity • TC = Tinned Copper

Hypalon is a DuPont trademark.

*Capacitance between conductors. **Capacitance between one conductor and other conductors connected to shield.

BELDENFor more information, contact **Belden Technical Support: 1-800-BELDEN-1 • www.belden.com****Belden114@cablcon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr**