

Security Composite Cable

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Plenum-Rated and Non-Plenum



Non-Plenum Composite Coax plus Twisted Pair

CM FT1 or CMG-LS FT4 Rated

Product Description

Coax: Solid bare copper conductor, foam polyolefin insulation, bare copper braid shield. Black PVC jacket (1306SB has Black LSZH jacket).

Pair: Stranded bare copper conductor, PVC insulation, Black PVC jacket. (1306SB has polypropylene insulation. Black LSZH jacket.) Color coded: Black & Red.

Plenum-Rated Composite Coax plus Twisted Pair

CMP FT6 Rated

Product Description

Coax: Solid bare copper conductor, FEP insulation, bare copper braid shield, Natural Flamarrest® jacket.

Pair: Stranded FEP insulation, Natural Flamarrest jacket. Color coded: Black & Red.

Coax and pair in Siamese configuration.
Sequential footage marking every two feet.

Specifications

Conductor	Bare Copper
Insulation (Non-Plenum)	
Coax	FPO
Pair	PVC
Insulation (Plenum)	FEP
Shield (Coax)	Bare Copper Braid
Jacket	
Non-Plenum	PVC
Plenum	Flamarrest
Approvals (Non-Plenum)	
NEC	CM
CEC	CM FT1
Approvals (LSZH)	
NEC	CMG-LS
CEC	CMG-LS FT4 Limited Smoke
Approvals (Plenum)	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Nominal Impedance (Coax)	75Ω
Temperature Rating	75°C

Applications

- CCTV plus Audio or Power
- Pan, Tilt and Zoom CCTV Control



Part No.	AWG	Stranding and Conductor	Shield/Braid Coverage	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
				Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

CM-Rated Composite (NEC CM and CEC CM FT1)

Mini RG-59 Type											
579945 new	25(cx)	solid BC	95% BC	.085	2.16	.151	3.84	500	152	15.0	6.8
	20(pr)	7/w BC	unshielded	.056	1.42	x	x	1000	305	29.0	13.2
						.332	8.43				

RG-59 Type											
549945	20(cx)	solid BC	95% BC	.145	3.68	.232	5.89	500	152	30.0	13.6
	18(pr)	7/w BC	unshielded	.066	1.68	x	x	1000	305	60.0	27.3
						.460	11.68				

RG-6 Type											
539945	18(cx)	solid BC	95% BC	.180	4.57	.266	6.76	500	152	34.0	15.5
	18(pr)	7/w BC	unshielded	.066	1.68	x	x	1000	305	69.0	31.3
						.500	12.70				

CMG-LS -Rated Composite (NEC CMG-LS and CEC CMG-LS FT4 Limited Smoke)

RG-6 Type											
1306SB new	18(cx)	solid BC	95% BC	.180	4.57	.275	6.99	500	152	37.0	16.8
	18(pr)	7/w BC	unshielded	.059	1.59	x	x	1000	305	76.0	34.5
						.514	13.06				

Plenum-Rated Composite (NEC CMP and CEC CMP FT6)

Mini RG-59 Type											
679948* new	25(cx)	solid BC	95% BC	.078	1.98	.144	3.66	500	152	16.5	7.4
	20(pr)	7/w BC	unshielded	.048	1.22	x	x	1000	305	34.0	15.5
						.328	8.33				

RG-59 Type											
649948	20(cx)	solid BC	95% BC	.134	3.40	.199	5.05	500	152	29.0	13.2
	18(pr)	7/w BC	unshielded	.059	1.50	x	x	1000	305	54.0	24.5
						.383	9.72				

RG-6 Type											
639948	18(cx)	solid BC	95% BC	.170	4.32	.232	5.89	500	152	32.0	14.5
	18(pr)	7/w BC	unshielded	.059	1.50	x	x	1000	305	60.0	27.2
						.416	10.57				

BC = Bare Copper • cx = Coax • pr = Pair • LSZH = Low-Smoke, Zero-Halogen

*679948 also available in White.

Security UTP Cable

CCTV Fixed and PTZ Applications
Riser-Rated



Non-Plenum

CM FT1 or CMR FT4 Rated

Product Description


Solid bare copper conductors, unshielded twisted pairs, polyolefin insulation, PVC jacket with rip cord. Sequential footage marking every two feet.

Specifications

Conductor	Solid Bare Copper
Shield	Unshielded
Jacket	PVC
Approvals	CM or CMR NEC CEC
Nominal Impedance	100Ω
Temperature Rating	80°C

Applications:

- 100BaseTX
- 100BaseVG ANYLAN
- 155ATM
- 622ATM
- AES/EBU
- Digital Video, RS-422
- Gigabit Ethernet
- NTSC/PAL Component or Composite Video
- Premise Horizontal Cable
- CCTV UTP
- PTZ
- Pan/Tilt/Zoom



Part No.	Component Descriptions	Insulation Material	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Non-Plenum (NEC CM and CEC CM FT1)

Category 5e										
1583A new	4-Pair UTP	Polyolefin	.008	0.20	.195	4.95	U-1000	U-305	21.0	9.5
	24 AWG						1000	305	21.0	9.5
	Solid						1640	500	34.4	15.7
	Bare Copper Cond.						3000	915	63.0	28.6
1500A new	4-Pair UTP	Polyolefin	.008	0.20	.200	5.08	A-1000	A-305	26.0	11.8
	24 AWG						1000	305	23.0	10.4
	Solid									
	Bare Copper Cond.									

Non-Plenum (NEC CMR and CEC CMR FT4)

Category 5e										
1583R new	4-Pair UTP	Polyolefin	.007	0.18	.197	5.00	U-1000	U-305	22.0	10.0
	24 AWG						1000	305	22.0	10.0
	Solid						3000	915	63.0	28.6
	Bare Copper Cond.									
1500R new	4-Pair UTP	Polyolefin	.007	0.18	.194	5.00	A-1000	A-305	27.0	12.2
	24 AWG						1000	305	24.0	10.9
	Solid									
	Bare Copper Cond.									
Category 6										
7881A new	4-Pair UTP	Polyolefin	.010	0.18	.235	5.97	A-1000	A-305	33.0	15.0
	23 AWG						1000	305	30.0	13.6
	Solid									
	Bare Copper Cond.									

UTP = Unshielded Twisted Pair

Refer to www.belden.com for jacket colors and put-ups.

Color Code Chart

Pair No.	Color Combinations
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

견적문의 Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr

Security UTP Cable

CCTV Fixed and PTZ Applications
Plenum-Rated



Plenum-Rated

CMP FT6 Rated

Product Description


Solid bare copper conductors, unshielded twisted pairs, FEP Teflon® insulation, Flamarrest® jacket with rip cord. Sequential footage marking every two feet.

Specifications

Conductor	Solid Bare Copper
Shield	Unshielded
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Nominal Impedance	100Ω
Temperature Rating	75°C

Applications:

- 100BaseTX
- 100BaseVG ANYLAN
- 155ATM
- 622ATM
- AES/EBU
- Digital Video, RS-422
- Gigabit Ethernet
- NTSC/PAL Component or Composite Video
- Premise Horizontal Cable
- CCTV UTP
- Pan/Tilt/Zoom (PTZ)



Part No.	Component Descriptions	Insulation Material	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Plenum-Rated (NEC CMP and CEC CMP FT6)

Category 5e										
1585A new	4-Pair UTP 24 AWG Solid Bare Copper Cond.	FEP Teflon	.007	0.18	.195	4.95	U-1000 1000 3000	U-305 305 915	23.0 24.0 69.0	10.4 10.9 31.3
1501A new	4-Pair UTP 24 AWG Solid Bare Copper Cond.	FEP Teflon	.008	0.20	.195	4.95	A-1000 1000	A-305 305	26.0 23.0	11.8 10.4
Category 6										
7882A new	4-Pair UTP 23 AWG Solid Bare Copper Cond.	FEP Teflon	.009	0.23	.224	5.69	A-1000 1000	A-305 305	32.0 29.0	14.5 13.2

UTP = Unshielded Twisted Pair

Refer to www.belden.com for jacket colors and put-ups.

Color Code Chart

Pair No.	Color Combinations
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Teflon is a DuPont trademark.

BELDEN

For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

견적문의 Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr

Pan/Tilt/Zoom Banana Peel® Composite

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Riser-Rated



Composite Coax, Pair and Multi-Conductors

CMR/CMG FT4 Rated

Product Description

(1) Coax: 20 AWG solid bare copper conductor, gas-injected foam high-density polyethylene insulation, bare copper braid shield (95% coverage), Black PVC jacket.

(1) Pair: 23 AWG solid bare copper conductors, polyolefin insulation, Blue PVC jacket. Color code: White/Blue Stripe & Blue. Category 5e tested.


(2) Conductors: 18 AWG stranded (7x26) bare copper conductors, PVC insulation, White flame-retardant PVC jacket. Color code: Black & Red.

Specifications

Conductor	Bare Copper
Application Shielding	
Video	Bare Copper Braid
Control	Unshielded
Power	Unshielded
Component Jackets	PVC
Overall Jacket	None
Approvals	
NEC	CMR
CEC	CMG FT4
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- CCTV plus Control and Power
- Pan, Tilt and Zoom CCTV Control



Part No.	Component Descriptions	Insulation Material & Shielding	Component Nom. OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Composite (NEC CMR and CEC CMG FT4)

RG-59/U 20 AWG Coax • Cat. 5e 23 AWG Pair • 18 AWG Cond.										
500PTZ new	(1) Coax: RG-59/U 20 AWG (solid) Bare Copper Cond.	Gas-injected Foam HDPE, Bare Copper Braid Shield (95% coverage)	.227	5.57	.411	10.4	500	152	38.5	17.5
	(1) 1-Pair 23 AWG (solid) Bare Copper Cond.	Polyolefin, Unshielded	.118	3.00			1000	305	71.0	32.3
	(1) 2-Cond. 18 AWG Stranded (7x26) Bare Copper Cond.	PVC, Unshielded	.171	4.34						

HDPE = High-density Polyethylene

U.S. Patent 7,049,523

Individual Cable Jacket Color Coding System

Jacket Color	Cable Type
Black	Coax, RG-59/U, 20 AWG, 95% Braid
Blue	1/P, 23 AWG, Unshielded
White	2/C, 18 AWG, Unshielded

Pan/Tilt/Zoom Banana Peel® Composite

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Plenum-Rated



Composite Coax, Pair and Multi-Conductors CMP FT6 Rated

Product Description

(1) **Coax:** 20 AWG solid bare copper conductor, Foam Perfluoroalkoxy (FPFA) insulation, bare copper braid shield (95% coverage), Black Flamarrest® jacket.

(1) **Pair:** 23 AWG solid bare copper conductors, FEP insulation, Blue Flamarrest jacket. Color code: White/Blue Stripe & Blue. Category 5e tested.


(2) **Conductors:** 18 AWG stranded (7x26) bare copper conductors, Flamarrest insulation, White Flamarrest jacket. Color code: Black & Red.

Specifications

Conductor	Bare Copper
Application Shielding	
Video	Bare Copper Braid
Control	Unshielded
Power	Unshielded
Component Jackets	Flamarrest
Overall Jacket	None
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- CCTV plus Control and Power
- Pan, Tilt and Zoom CCTV Control



Part No.	Component Descriptions	Insulation Material & Shielding	Component Nom. OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Plenum-rated Composite (NEC CMP and CEC CMP FT6)

RG-59/U 20 AWG Coax • Cat. 5e 23 AWG Pair • 18 AWG Cond.										
600PTZ NEW	(1) Coax: RG-59/U 20 AWG (solid) Bare Copper Cond.	FPFA, Bare Copper Braid Shield (95% coverage)	.193	4.90	.351	8.9	500	152	38.5	17.5
	(1) 1-Pair 23 AWG (solid) Bare Copper Cond.	FEP, Unshielded	.116	2.95			1000	305	71.0	32.2
	(1) 2-Cond. 18 AWG Stranded (7x26) Bare Copper Cond.	Flamarrest, Unshielded	.158	4.01						

FEP = Fluorinated Ethylene Propylene • FPFA = Foam Perfluoroalkoxy

U.S. Patent 7,049,523

Individual Cable Jacket Color Coding System

Jacket Color	Cable Type
Black	Coax, RG-59/U, 20 AWG, BC Braid (95%)
Blue	1/P, 23 AWG, Unshielded
White	2/C, 18 AWG, Unshielded

Pan/Tilt/Zoom Banana Peel® Composite

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Riser-Rated



Composite Coax, Pair and Multi-Conductors

CMR/CMG FT4 Rated

Product Description

(1) Coax: 20 AWG solid bare copper conductor, gas-injected foam high-density polyethylene insulation, bare copper braid shield (95% coverage), Black PVC jacket.

(1) Pair: 22 AWG stranded (7x30) bare copper conductors, polyolefin insulation, Beldfoil® shield (100% coverage), Blue PVC jacket. Color code: White/Blue Stripe & Blue. Category 5e tested.


(2) Conductors: 18 AWG stranded (7x26) bare copper conductors, PVC insulation, White flame-retardant PVC jacket. Color code: Black & Red.

Specifications

Conductor	Bare Copper
Application Shielding	
Video	Bare Copper Braid
Control	Aluminum/Polyester
Power	Unshielded
Component Jackets	PVC
Overall Jacket	None
Approvals	
NEC	CMR
CEC	CMG FT4
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- CCTV plus Control and Power
- Pan, Tilt and Zoom CCTV Control



Part No.	Component Descriptions	Insulation Material & Shielding	Component Nom. OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Composite (NEC CMR and CEC CMG FT4)

RG-59/U 20 AWG Coax • Cat. 5e 22 AWG Pair • 18 AWG Cond.										
501PTZ new	(1) Coax: RG-59/U 20 AWG (solid) BC Cond.	Gas-injected Foam HDPE, BC Braid Shield (95% coverage)	.227	5.57	.419	10.6	500	152	41.0	18.6
	(1) 1-Pair 22 AWG (7x30) BC Cond.	Polyolefin, Beldfoil Shield (100% coverage)	.177	4.50			1000	305	76.0	34.5
	(1) 2-Cond. 18 AWG Stranded (7x26) BC Cond.	PVC, Unshielded	.171	4.34						

BC = Bare Copper • HDPE = High-density Polyethylene

U.S. Patent 7,049,523

Individual Cable Jacket Color Coding System

Jacket Color	Cable Type
Black	Coax: RG-59/U, 20 AWG, BC Braid Shield
Blue	1/P, 22 AWG, Beldfoil Shield
White	2/C, 18 AWG, Unshielded

Pan/Tilt/Zoom Banana Peel® Composite

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Plenum-Rated



Composite Coax, Pair and Multi-Conductors

CMP FT6 Rated

Product Description

(1) **Coax:** 20 AWG solid bare copper conductor, Foam Perfluoroalkoxy (FPFA) insulation, bare copper braid shield (95% coverage), Black Flamarrest® jacket.

(1) **Pair:** 22 AWG stranded (7x30) bare copper conductors, FEP insulation, Beldfoil® shield (100% coverage), Blue Flamarrest jacket. Color code: White/Blue Stripe & Blue. Category 5e tested.


(2) **Conductors:** 18 AWG stranded (7x26) bare copper conductors, Flamarrest insulation, White Flamarrest jacket. Color code: Black & Red.

Specifications

Conductor	Bare Copper
Application Shielding	
Video	Bare Copper Braid
Control	Aluminum/Polyester
Power	Unshielded
Component Jackets	Flamarrest
Overall Jacket	None
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- CCTV plus Control and Power
- Pan, Tilt and Zoom CCTV Control



Part No.	Component Descriptions	Insulation Material & Shielding	Component Nom. OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Plenum-rated Composite (NEC CMP and CEC CMP FT6)

RG-59/U 20 AWG Coax • Cat. 5e 22 AWG Pair • 18 AWG Cond.										
601PTZ new	(1) Coax: RG-59/U 20 AWG (solid) BC Cond.	FPFA, BC Braid Shield (95% coverage)	.193	4.90	.351	8.9	500	152	40.0	18.2
	(1) 1-Pair 22 AWG (7x30) BC Cond.	FEP, Beldfoil Shield (100% coverage)	.116	2.95			1000	305	73.0	33.2
	(1) 2-Cond. 18 AWG Stranded (7x26) BC Cond.	Flamarrest, Unshielded	.158	4.01						

BC = Bare Copper • FEP = Fluorinated Ethylene Propylene • FPFA = Foam Perfluoroalkoxy

U.S. Patent 7,049,523

Individual Cable Jacket Color Coding System

Jacket Color	Cable Type
Black	Coax: RG-59/U, 20 AWG, BC Braid Shield
Blue	1/P, 22 AWG, Beldfoil Shield
White	2/C, 18 AWG, Unshielded

Pan/Tilt/Zoom Banana Peel® CompositeCCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Riser-Rated**Composite Coax,
Pair and Multi-Conductors**
CMR/CMG FT4 Rated**Product Description**

(1) Coax: 20 AWG solid bare copper conductor, gas-injected foam high-density polyethylene insulation, bare copper braid shield (95% coverage), Black PVC jacket.

(1) Pair: 18 AWG stranded (19x30) bare copper conductors, polyolefin insulation, Beldfoil® shield (100% coverage), Blue PVC jacket. Color code: White/Blue Stripe & Blue. Category 5e tested.


(2) Conductors: 18 AWG stranded (7x26) bare copper conductors, PVC insulation, White flame-retardant PVC jacket. Color code: Black & Red.

Specifications

Conductor	Bare Copper
Application Shielding	
Video	Bare Copper Braid
Control	Aluminum/Polyester
Power	Unshielded
Component Jackets	PVC
Overall Jacket	None
Approvals	
NEC	CMR
CEC	CMG FT4
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- CCTV plus Control and Power
- Pan, Tilt and Zoom CCTV Control



Part No.	Component Descriptions	Insulation Material & Shielding	Component Nom. OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Composite (NEC CMR and CEC CMG FT4)

RG-59/U 20 AWG Coax • Cat. 5e 18 AWG Pair • 18 AWG Cond.										
502PTZ new	(1) Coax: RG-59/U 20 AWG (solid) BC Cond.	Gas-injected Foam HDPE, BC Braid Shield (95% coverage)	.227	5.57	.451	11.5	500	152	50.0	22.7
	(1) 1-Pair 18 AWG (19x30) BC Cond.	Polyolefin, Beldfoil Shield (100% coverage)	.219	5.56			1000	305	94.0	42.6
	(1) 2-Cond. 18 AWG Stranded (7x26) BC Cond.	PVC, Unshielded	.171	4.34						

BC = Bare Copper • HDPE = High-density Polyethylene

U.S. Patent 7,049,523

Individual Cable Jacket Color Coding System

Jacket Color	Cable Type
Black	Coax: RG-59/U, 20 AWG, BC Braid Shield
Blue	1/P, 18 AWG, Beldfoil Shield
White	2/C, 18 AWG, Unshielded

Pan/Tilt/Zoom Banana Peel® Composite

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Plenum-Rated



Composite Coax, Pair and Multi-Conductors CMP FT6 Rated

Product Description

(1) Coax: 20 AWG solid bare copper conductors, Foam Perfluoroalkoxy (FPFA) insulation, bare copper braid shield (95% coverage), Black Flamarrest® jacket.

(1) Pair: 18 AWG stranded (19x30) bare copper conductor, FEP insulation, Beldfoil® shield (100% coverage), Blue Flamarrest jacket. Color code: White/Blue Stripe & Blue. Category 5e tested.


(2) Conductors: 18 AWG stranded (7x26) bare copper conductors, Flamarrest insulation, White Flamarrest jacket. Color code: Black & Red.

Specifications

Conductor	Bare Copper
Application Shielding	
Video	Bare Copper Braid
Control	Aluminum/Polyester
Power	Unshielded
Component Jackets	Flamarrest
Overall Jacket	None
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- CCTV plus Control and Power
- Pan, Tilt and Zoom CCTV Control



Part No.	Component Descriptions	Insulation Material & Shielding	Component Nom. OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Plenum-rated Composite (NEC CMP and CEC CMP FT6)

RG-59/U 20 AWG Coax • Cat. 5e 18 AWG Pair • 18 AWG Cond.										
602PTZ new	(1) Coax: RG-59/U 20 AWG (solid) BC Cond.	FPFA, BC Braid Shield (95% coverage)	.193	4.90	.363	9.2	500 1000	152 305	42.5 79.0	19.3 35.8
	(1) 1-Pair 18 AWG (19x30) BC Cond.	FEP, Beldfoil Shield (100% coverage)	.150	3.81						
	(1) 2-Cond. 18 AWG Stranded (7x26) BC Cond.	Flamarrest, Unshielded	.158	4.01						

BC = Bare Copper • FEP = Fluorinated Ethylene Propylene • FPFA = Foam Perfluoroalkoxy

Individual Cable Jacket Color Coding System

Jacket Color	Cable Type
Black	Coax: RG-59/U, 20 AWG, BC Braid Shield
Blue	1/P, 18 AWG, Beldfoil Shield
White	2/C, 18 AWG, Unshielded

US Patent 7,049,523

BELDEN

For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com




견적문의 Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr

UTP CCTV Surveillance CablesCCTV and PTZ Applications
Unshielded, Riser-Rated**Composite
Unshielded Multi-conductor**
CMR/CMG FT4 Rated**Product Description****Data Pair:** 24 or 23 AWG solid bare copper conductors, unshielded twisted pairs, polyolefin insulation.**Power Conductors:** 16 AWG stranded (19x29) tinned copper conductors, unshielded, polypropylene insulation.**Overall:** White or Black, flame-retardant PVC jacket.**Specifications**

Conductor	
Data Pair	Solid Bare Copper
Power	Stranded Tinned Copper
Shield	Unshielded
Jacket	F-R PVC
Approvals	
NEC	CMR
CEC	CMG FT4
NEC Articles	800
Nominal Impedance	100Ω
Temperature Rating	75°C

Applications:

- UTP-CCTV
- CCTV
- CCTV on UTP
- CCTV Video/Control
- Closed Circuit Television
- Pan/Tilt/Zoom (PTZ) Cameras
- Surveillance
- Video Over Twisted Pairs

5284UE (Round Construction)**5284US (Siamese Construction)****5288US (Siamese Construction)**

Part No.	Component Descriptions	Insulation Material	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Unshielded Composite (NEC CMR and CEC CMG FT4)**Category 5e**

5284UE new	2-Pair UTP 23 AWG Solid Bare Copper Cond.	Polyolefin	.040	1.01	.233	5.92	500 1000	152 305	22.5 44.0	10.2 20.0
	2-Cond. 16 AWG Stranded (19x29) Tinned Copper Cond.	Polypropylene	.077	1.96						
5284US new	2-Pair UTP 24 AWG Solid Bare Copper Cond.	Polyolefin	.035	.89	.208 x .426	5.28 x 10.82	500 100	152 305	25.5 44.0	11.6 20.0
	2-Cond. 16 AWG Stranded (19x29) Tinned Copper Cond.	PVC	.080	2.03						
5288US* new	4-Pair UTP 24 AWG Solid Bare Copper Cond.	Polyolefin	.035	.89	.198 x .424	5.03 x 10.77	500 1000	152 305	27.5 52.0	12.5 23.6
	2-Cond. 16 AWG Stranded (19x29) Tinned Copper Cond.	PVC	.080	2.03						

UTP = Unshielded Twisted Pair • F-R = Flame-retardant

*Special Construction available upon request.

Color Code Chart (Data Pair)

Pair No.	Color
1	Blue & White/Blue Stripe
2	Orange & White/Orange Stripe
3	Green & White/Green Stripe
4	Brown & White/Brown Stripe

Color Code Chart (Power)

Cond. No.	Color
1	Black
2	Red

UTP CCTV Surveillance Cables

CCTV and PTZ Applications
Unshielded, Plenum-Rated



Composite Unshielded Multi-conductor CMP Rated

Product Description

Data Pair: 24 or 23 AWG solid bare copper conductors, unshielded twisted pairs, FEP insulation.

Power Conductors: 16 AWG stranded (19x29) tinned copper conductors, unshielded, FEP or Flamarrest® insulation.

Overall: White or Black, Flamarrest jacket.


Specifications

Conductor	
Data Pair	Solid Bare Copper
Power	Stranded Tinned Copper
Shield	Unshielded
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP
NEC Articles	800
Nominal Impedance	100Ω
Temperature Rating	75°C


Applications:

- UTP-CCTV
- CCTV
- CCTV on UTP
- CCTV Video/Control
- Closed Circuit Television
- Pan/Tilt/Zoom (PTZ) Cameras
- Surveillance
- Video Over Twisted Pairs


6284UE (Round Construction)



6284US (Siamese Construction)



6288US (Siamese Construction)



Part No.	Component Descriptions	Insulation Material	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Unshielded Composite (NEC CMP and CEC CMP)

Category 5e										
6284UE new	2-Pair UTP 23 AWG Solid Bare Copper Cond.	FEP	.041	1.04	.220	5.59	500	152	19.5	8.8
							1000	305	38.0	17.2
	2-Cond. 16 AWG Stranded (19x29) Tinned Copper Cond.	FEP	.077	1.96						
6284US new	2-Pair UTP 24 AWG Solid Bare Copper Cond.	FEP	.035	.89	.173 x .358	4.39 x 9.09	500	152	26.0	11.8
							1000	305	50.0	22.7
	2-Cond. 16 AWG Stranded (19x29) Tinned Copper Cond.	Flamarrest	.077	1.96						
6288US new	4-Pair UTP 23 AWG Solid Bare Copper Cond.	FEP	.042	1.07	.222 x .450	5.64 x 11.43	500	152	34.5	15.7
							1000	305	66.0	29.9
	2-Cond. 16 AWG Stranded (19x29) Tinned Copper Cond.	Flamarrest	.077	1.96						

FEP = Fluorinated Ethylene Propylene • UTP = Unshielded Twisted Pair

Color Code Chart (Data Pair)

Pair No.	Color
1	Blue & White/Blue Stripe
2	Orange & White/Orange Stripe
3	Green & White/Green Stripe
4	Brown & White/Brown Stripe

Color Code Chart (Power)

Cond. No.	Color
1	Black
2	Red

UTP CCTV Surveillance Cables

CCTV Fixed and PTZ Applications
Unshielded, Non-Plenum



Unshielded Twisted Pairs

CM FT1 or CMR Rated

Product Description


Solid bare copper conductors, unshielded twisted pairs, polyolefin insulation, PVC jacket with rip cord. Sequential footage marking every two feet.

Specifications

Conductor	Solid Bare Copper
Shield	Unshielded
Jacket	PVC
Approvals	CM or CMR
NEC	CEC
CM FT1 or CMR FT4	
Nominal Impedance	100Ω
Temperature Rating	80°C

Applications:

- 100BaseTX
- 100BaseVG ANYLAN
- 155ATM
- 622ATM
- AES/EBU
- Digital Video, RS-422
- Gigabit Ethernet
- NTSC/PAL Component or Composite Video
- Premise Horizontal Cable
- CCTV UTP
- PTZ
- Pan/Tilt/Zoom



Part No.	Component Descriptions	Insulation Material	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Unshielded Twisted Pairs (NEC CM and CEC CM FT1)

Category 5e										
1583A new	4-Pair UTP	Polyolefin	.008	0.20	.195	4.95	U-1000	U-305	21.0	9.5
	24 AWG						1000	305	21.0	9.5
	Solid						1640	500	34.4	15.7
	Bare Copper Cond.						3000	915	63.0	28.6
1500A new	4-Pair UTP	Polyolefin	.008	0.20	.200	5.08	A-1000	A-305	26.0	11.8
	24 AWG						1000	305	23.0	10.4
	Solid									
	Bare Copper Cond.									

Unshielded Twisted Pairs (NEC CMR and CEC CMR FT4)

Category 5e										
1583R new	4-Pair UTP	Polyolefin	.007	0.18	.197	5.00	U-1000	U-305	23.0	10.4
	24 AWG						1000	305	22.0	10.0
	Solid						3000	915	63.0	28.6
	Bare Copper Cond.									
1500R new	4-Pair UTP	Polyolefin	.007	0.18	.194	5.00	A-1000	A-305	27.0	12.2
	24 AWG						1000	305	24.0	10.9
	Solid									
	Bare Copper Cond.									
Category 6										
7881A new	4-Pair UTP	Polyolefin	.010	0.18	.235	5.97	A-1000	A-305	33.0	15.0
	23 AWG						1000	305	30.0	13.6
	Solid									
	Bare Copper Cond.									

UTP = Unshielded Twisted Pair

Refer to www.belden.com for jacket colors and put-ups.

Color Code Chart

Pair No.	Color Combinations
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

견적문의 Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr

UTP CCTV Surveillance Cables

CCTV Fixed and PTZ Applications
Unshielded, Plenum-Rated



Unshielded Twisted Pairs

CMP FT6 Rated

Product Description


Solid bare copper conductors, unshielded twisted pairs, FEP Teflon® insulation, Flamarrest® jacket with rip cord. Sequential footage marking every two feet.

Specifications

Conductor	Solid Bare Copper
Shield	Unshielded
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Nominal Impedance	100Ω
Temperature Rating	75°C

Applications:

- 100BaseTX
- 100BaseVG ANYLAN
- 155ATM
- 622ATM
- AES/EBU
- Digital Video, RS-422
- Gigabit Ethernet
- NTSC/PAL Component or Composite Video
- Premise Horizontal Cable
- CCTV UTP
- Pan/Tilt/Zoom (PTZ)



Part No.	Component Descriptions	Insulation Material	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Unshielded Twisted Pairs (NEC CMP and CEC CMP FT6)

Category 5e										
1585A new	4-Pair UTP 24 AWG Solid Bare Copper Cond.	FEP Teflon®	.007	0.18	.195	4.95	U-1000 1000 3000	U-305 305 915	23.0 24.0 69.0	10.4 10.9 31.3
1501A new	4-Pair UTP 24 AWG Solid Bare Copper Cond.	FEP Teflon	.008	0.20	.195	4.95	A-1000 1000	A-305 305	27.0 24.0	12.2 10.9
Category 6										
7882A new	4-Pair UTP 23 AWG Solid Bare Copper Cond.	FEP Teflon	.009	0.23	.224	5.69	A-1000 1000	A-305 305	34.0 31.0	15.4 14.1

UTP = Unshielded Twisted Pair

Refer to www.belden.com for jacket colors and put-ups.

Color Code Chart

Pair No.	Color Combinations
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Teflon is a DuPont trademark.



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

견적문의 Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr