

Security Coaxial Cable

Surveillance and CCTV Applications
Limited Combustible



Limited Combustible Coax

FHC 25/50 CMP

Product Description

Bare copper conductor, foam FEP insulation, bare copper braid shield (95% coverage). Black FEP jacket. Sequential footage marking every two feet.


Specifications

Conductor	Bare Copper
Insulation	FFEP
Shield	Bare Copper Braid
Jacket	FEP
Approvals	NEC
NEC Articles	CMP FHC 25/50
NEC Articles	800
Nominal Impedance	75Ω
Temperature Rating	200°C

Applications

- CCTV
- Video Security Coax

Solid Conductor



Part No.	AWG	Stranding and Conductor	Shield/Braid Coverage	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
				Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Limited Combustible Coax (CMP FHC 25/50)

RG-59/U Type

7986LC	20	solid	95%	.135	3.43	.193	4.90	500	152	17.0	7.7
NEW		BC	BC					1000	305	31.0	14.1

RG-6/U Type

7985LC	18	solid	95%	.170	4.31	.228	5.79	500	152	22.0	10.0
NEW		BC	BC					1000	305	44.0	20.0

BC = Bare Copper • FEP = Fluorinated Ethylene Propylene