


## Overall Shield

Data Cables for Molex SEMMCONN and AMP® SDL Connectors

Computers, Instrumentation and Medical Electronics Interconnect Cables

| Description   | Part No.     | UL NEC/<br>C(UL) CEC<br>Type | No.<br>of<br>Cond. | Color<br>Code  | Standard Lengths |                | Standard<br>Unit Weight |             | Insulation<br>Thickness |             | Jacket<br>Thickness |      | Nominal OD |    |
|---|--------------|------------------------------|--------------------|--|------------------|----------------|-------------------------|-------------|-------------------------|-------------|---------------------|------|------------|----|
|   |              |                              |                    |  | Ft.              | m              | Lbs.                    | kg          | Inch                    | mm          | Inch                | mm   | Inch       | mm |
| <b>26 AWG Stranded (7x34) Tinned Copper Conductors • Duofoil® Shield (100% Coverage) • 26 AWG Stranded Tinned Copper Drain Wire</b> |              |                              |                    |  |                  |                |                         |             |                         |             |                     |      |            |    |
| <b>PVC Insulation • Black PVC Jacket</b>  |              |                              |                    |  |                  |                |                         |             |                         |             |                     |      |            |    |
| UL AWM Style 2464<br>(300V 80°C)<br>VW-1<br>       | <b>1211A</b> | NEC:<br>CL2X                 | 4                  | White,<br>Yellow,<br>Orange,<br>Green  | 500<br>1000      | 152.4<br>304.8 | 12.0<br>23.0            | 5.4<br>10.4 | .015<br>.38             | .036<br>.91 | .195                | 4.95 |            |    |
|   | <b>1212A</b> | NEC:<br>CL2X                 | 6                  | Red, Blue,<br>Green,<br>Orange,<br>Yellow,<br>White  | 500<br>1000      | 152.4<br>304.8 | 14.5<br>30.0            | 6.6<br>13.6 | .015<br>.38             | .037<br>.93 | .220                | 5.59 |            |    |
|   | <b>1213A</b> | NEC:<br>CL2X                 | 8                  | Black,<br>Purple,<br>Red, Blue,<br>Green,<br>Orange,<br>Yellow,<br>White   | 500<br>1000      | 152.4<br>304.8 | 12.0<br>24.0            | 5.4<br>10.4 | .015<br>.38             | .039<br>.98 | .239                | 6.07 |            |    |
|   | <b>1214A</b> | NEC:<br>CL2X                 | 16                 | White & Red,<br>White & Brown,<br>White & Black,<br>Black, Red,<br>Brown,<br>Purple, Blue,<br>Green, Gray,<br>Aqua, Tan,<br>Pink, Orange,<br>White, Yellow | 1000             | 304.8          | 57.0                    | 25.9        | .015<br>.38             | .035<br>.89 | .301                | 7.65 |            |    |

AMP is a registered trademark of AMP, Inc.

**BELDEN**

For more information, contact Belden Technical Support: 1-800-BELDEN-1 • [www.belden.com](http://www.belden.com)

[Belden114@CableCon.kr](mailto:Belden114@CableCon.kr) / 0707-434-7704 / Fax. 02-744-0909 / [www.CableCon.co.kr](http://www.CableCon.co.kr)