


Individually Shielded

Audio, Control and Instrumentation Cables


Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

22 AWG Stranded (7x30) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 22 AWG Stranded TC Drain Wire

Polypropylene Insulation • Chrome PVC Jacket

 <p>Z-Fold®</p>	UL AWM Style 2919 (30V 80°C)	8777	NEC: 3 CM CEC: CM	See Chart 3 (Tech Info Section)	100 250 U-500 500 U-1000 1000 1640 3280 5000 10000††	30.5 76.2 U-152.4 152.4 U-304.8 304.8 499.9 999.7 1524.0 3048.0	4.7 10.0 21.0 20.0 41.0 44.0 70.5 141.0 215.0 460.0	2.1 4.5 9.5 9.1 18.6 20.0 32.0 64.0 97.6 208.8	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.273 6.93	50	66%	30	98	55	180	
	For Plenum versions of 8777, see 88777, 87777 or 82777.																	
			8778	NEC: 6 CM CEC: CM	See Chart 3 (Tech Info Section)	100 250 500 1000	30.5 76.2 152.4 304.8	8.4 19.0 43.0 83.0	3.8 8.6 19.5 37.7	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.362 9.19	50	66%	30	98	55	180
	For Plenum versions of 8778, see 88778, 87778 or 82778.																	
			8774	NEC: 9 CM CEC: CM	See Chart 3 (Tech Info Section)	100 250 500 1000	30.5 76.2 152.4 304.8	11.5 29.5 57.5 113.0	5.2 13.4 26.1 51.3	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.417 10.59	50	66%	30	98	55	180
			8775	NEC: 11 CM CEC: CM	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	12.1 65.5 130.0	5.5 29.7 59.0	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.464 11.79	50	66%	30	98	55	180
			9768	NEC: 12 CM CEC: CM	See Chart 3 (Tech Info Section)	100 250 500 1000	30.5 76.2 152.4 304.8	13.2 36.5 73.5 143.0	6.0 16.5 33.4 65.0	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.464 11.79	50	66%	30	98	55	180
			8776	NEC: 15 CM CEC: CM	See Chart 3 (Tech Info Section)	100 250 500 1000	30.5 76.2 152.4 304.8	17.8 49.5 98.0 197.0	8.1 22.5 44.5 89.5	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.548 13.92	50	66%	30	98	55	180
			9769	NEC: 17 CM CEC: CM	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	20.0 109.0 215.0	9.1 49.5 97.7	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.577 14.66	50	66%	30	98	55	180
			8769	NEC: 19 CM CEC: CM	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	22.9 123.0 244.0	10.4 55.8 110.8	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.603 15.32	50	66%	30	98	55	180
		8773	NEC: 27 CM CEC: CM	See Chart 3 (Tech Info Section)	100 250† 500 1000	30.5 76.2 152.4 304.8	33.9 83.8 163.0 341.0	15.4 38.0 74.0 154.8	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.709 18.00	50	66%	30	98	55	180	
		9767	NEC: 37 CM CEC: CM	See Chart 3 (Tech Info Section)	500† 1000†	152.4 304.8	224.0 481.0	101.8 218.6	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.800 20.32	50	66%	30	98	55	180	

Polypropylene Insulation • Black Low-Smoke, Zero-Halogen Jacket

 <p>Z-Fold®</p>	U300V RMS, Non-conduit	8777SB	NEC: 3 CMG-LS CEC: CMG-LS FT4 Limited Smoke	See Chart 3 (Tech Info Section)	U-500† U-1000 1000†	U-152.4 U-304.8 304.8	19.5 38.0 39.0	8.9 17.3 17.7	15.0Ω/M' 49.2Ω/km	10.6Ω/M' 34.8Ω/km	.273 6.93	50	66%	30	98	55	180
---	------------------------	---------------	---	--	---------------------------	-----------------------------	----------------------	---------------------	----------------------	----------------------	--------------	----	-----	----	----	----	-----

DCR = DC Resistance • TC = Tinned Copper

See Attenuation, Rise Time and Bit Rate Data for this series on page 5.39.

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

† Spools are one piece, but length may vary -0 to +20% from length shown.

†† Final put-up length may vary -10% to +20% from length shown. May contain 2 pieces. Minimum length of any one piece is 1500 ft.



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com