

3-Conductor

UL/CSA Types: S, SO, SJ

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm

S Rubber Jacket • Smooth Jacket • UL/CSA Listed**600V, 60°C** • Cotton Serve Separator • Color Code: Black, White, Green

19109	250 [†]	76.2	18.8	8.5	Black	18 (42x34) BC	.032	.81	.065	1.65	.380	9.65
19108	250 [†]	76.2	27.5	12.5	Black	16 (65x34) BC	.033	.84	.065	1.65	.405	10.29

600V, 60°C • Paper Tape Separator • Color Code: Black, White, Green

19107	250 [†]	76.2	42.3	19.2	Black	14 (41x30) BC	.048	1.22	.085	2.16	.535	13.59
19106	250 [†]	76.2	61.8	28.1	Black	12 (65x30) BC	.051	1.30	.099	2.51	.640	16.26
19105	250 [†]	76.2	78.0	35.5	Black	10 (105x30) BC	.050	1.27	.099	2.51	.681	17.30

SO Oil-Resistant Rubber Jacket • Smooth Jacket • UL/CSA Listed**600V, 90°C** • Cotton Serve Separator • Color Code: Black, White, Green

19209	250 [†]	76.2	19.3	8.8	Black	18 (42x34) BC	.032	.81	.065	1.65	.380	9.65
19208	250 [†]	76.2	26.5	12.0	Black	16 (65x34) BC	.033	.84	.063	1.60	.400	10.16

600V, 90°C • Paper Tape Separator • Color Code: Black, White, Green

19207	250 [†]	76.2	43.5	19.7	Black	14 (41x30) BC	.048	1.22	.086	2.18	.538	13.67
19206	250 [†]	76.2	62.8	28.5	Black	12 (65x30) BC	.051	1.30	.100	2.54	.632	16.05
19205	250 [†]	76.2	79.3	36.0	Black	10 (105x30) BC	.050	1.27	.099	2.51	.681	17.30

SJ Rubber Jacket • Smooth Jacket • UL/CSA Listed**300V, 60°C** • Paper Tape Separator • Color Code: Black, White, Green

19129	250 [†]	76.2	13.8	6.3	Black	18 (16x30) BC	.031	.79	.039	.99	.315	8.00
19125	250 [†]	76.2	13.5	6.1	Black	18 (42x34) BC	.032	.81	.038	.97	.315	8.00
19130	250 [†]	76.2	17.5	7.9	Black	16 (26x30) BC	.031	.79	.038	.97	.340	8.64
19124	250 [†]	76.2	16.5	7.5	Black	16 (65x34) BC	.033	.84	.038	.97	.340	8.64
8479	250	76.2	7.8	3.5	Black	14 (41x30) BC	.031	.79	.039	.99	.380	9.65

BC = Bare Copper

[†]Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.

3-Conductor

UL/CSA Types: SJO, SJT

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm

SJO Oil-Resistant Rubber Jacket • Smooth Jacket • UL/CSA Listed**300V, 90°C** • Paper Tape Separator • Color Code: Black, White, Green

19229	250 [†]	76.2	14.3	6.5	Black	18 (16x30) BC	.031	.79	.039	.99	.315	8.00
19230	250 [†]	76.2	17.8	8.1	Black	16 (26x30) BC	.031	.79	.038	.97	.340	8.64

SJT PVC Jacket • Serrated Jacket • UL/CSA Listed**300V, 60°C** • Paper Tape Separator • Color Code: Black, White, Green (18 AWG); Black, White, Green/Yellow (16 AWG)


19348	250 [†]	76.2	17.3	7.8	Gray, Black	18 (42x34) BC	.032	.81	.046	1.17	.328	8.33
19349	250 [†]	76.2	18.3	8.3	Gray, Black	16 (65x34) BC	.033	.83	.038	.97	.340	8.64

SJT PVC Jacket • Smooth Jacket • UL/CSA Listed**300V, 60°C** • Paper Tape Separator • International Color Code: Light Blue, Brown, Green/Yellow

19352	250	76.2	17.5	8.0	Black	18 (42x34) BC	.032	.81	.046	1.17	.328	8.33
19353	250	76.2	20.0	9.1	Black	16 (65x34) BC	.033	.84	.036	.91	.353	8.97
19354	250	76.2	25.0	11.4	Black	14 (41x30) BC	.033	.84	.038	.97	.380	9.65

SJT PVC Jacket • **Shielded** • Smooth Jacket • 20 AWG Drain Wire (7x28) • UL/CSA Listed**300V, 60°C Shielded** • Beldfoil® Shield (100% Coverage) • International Color Code: Light Blue, Brown, Green/Yellow

19362	250	76.2	17.3	7.8	Black	18 (42x34) BC	.032	.81	.050	1.27	.340	8.64
	500	152.4	35.0	15.9								
19363	250	76.2	21.3	9.7	Black	16 (65x34) BC	.033	.84	.047	1.19	.365	9.27
19364	250	76.2	26.3	11.9	Black	14 (41x30) BC	.033	.84	.042	1.07	.402	10.21

SJT PVC Jacket • **Low Leakage Power Cord** • Smooth Jacket • UL Listed**300V, 75°C** • Paper Tape Separator • Color Code: Black, White, Green

9998*	500 ^{††}	152.4	55.5	25.2	Gray	16 (65x34) Bare Copper	.033	.84	.045	1.14	.475	12.07
	1000 ^{††}	304.8	107.0	48.5	Lt. Blue							

BC = Bare Copper

*Not CSA recognized.


[†]Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.^{††}Put-ups may contain more than one piece. Minimum length of any one piece is 100 ft.

3-Conductor


UL/CSA Types: SJTOW, STOW, SV, SVT

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm


SJTOW Belflex® Premium PVC • Smooth Jacket • UL/CSA Listed**300V, 105°C • Paper Tape Separator • International Color Code: Light Blue, Brown, Green/Yellow**

	VW-1	19509*	250	76.2	14.0	6.4	Matte Black	18 (42x34) BC	.032	.81	.038	.97	.315	8.00
		19510*	250	76.2	17.5	7.9	Matte Black	16 (65x34) BC	.033	.84	.038	.97	.340	8.64
		19511*	250	76.2	23.8	10.8	Matte Black	14 (41x30) BC	.032	.81	.040	1.02	.380	9.65


STOW Belflex Premium PVC • Smooth Jacket • UL/CSA Listed**600V, 105°C • Paper Tape Separator • International Color Code: Light Blue, Brown, Green/Yellow**

	VW-1	19503*	250	76.2	19.0	8.6	Matte Black	18 (42x34) BC	.032	.81	.070	1.78	.380	9.65
		19504*	250	76.2	23.0	10.5	Matte Black	16 (65x34) BC	.033	.84	.070	1.78	.405	10.29
		19505*	250	76.2	42.5	19.3	Matte Black	14 (41x30) BC	.049	1.24	.089	2.26	.558	14.17


SV Rubber Jacket • Smooth Jacket • UL/CSA Listed**300V, 60°C • Cotton Serve Separator • Color Code: Black, White, Green**

		8453	100	30.5	4.9	2.2	Black	18 (41x34) TC	.018	.46	.036	.91	.256	6.50
			500	152.4	21.0	9.5								

SVT PVC Jacket • Serrated Jacket • UL/CSA Listed**300V, 60°C • Paper Tape Separator • Color Code: Black, White, Green**

		19350	250 [†]	76.2	10.8	4.9	Gray	18 (42x34) BC	.018	.46	.038	.97	.253	6.43

SVT PVC Jacket • Smooth Jacket • UL/CSA Listed**300V, 60°C • Paper Tape Separator • International Color Code: Light Blue, Brown, Green/Yellow**

		19402	250 [†]	76.2	12.3	5.6	Black	18 (42x34) BC	.018	.46	.034	.86	.253	6.43

BC = Bare Copper

*These constructions are approved as water-resistant, oil-resistant and for outdoor use.

[†]Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.

3-, 4- and 5-Conductor

UL/CSA Type: SVT, SO

UL AWM Styles: 4097 and 4256

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm

3-Conductor SVT PVC Jacket • Shielded • Smooth Jacket • 22 AWG Drain Wire (7x30) • UL/CSA Listed**300V, 60°C Shielded • Beldfoil® Shield (100% Coverage) • International Color Code: Light Blue, Brown, Green/Yellow**

19401	250 †	76.2	12.3	5.6	Black	18 (42x34) BC	.018	.46	.043	1.09	.270	6.86
	1000 ††	304.8	49.0	22.3								

300V, 60°C Shielded • Duofoil® Shield (100% Coverage) • Braid (88% Coverage) • Internat'l Color Code: Light Blue, Brown, Green/Yellow


19403	250 †	76.2	17.8	8.1	Black	18 (42x34) BC	.018	.46	.038	.97	.307	7.80

4-Conductor Rubber Jacket • Smooth Jacket • Style 4097**300V, 60°C • Paper Tape Separator • Color Code: Black, White, Brown, Red**

8454*	100	30.5	5.8	2.6	Black	18 (41x34) TC	.018	.46	.036	.91	.265	6.73
	U-500	U-152.4	27.0	12.3								
	500	152.4	25.0	11.3								
	U-1000	U-304.8	52.0	23.6								
	1000	304.8	54.0	24.5								

4-Conductor SO Oil-Resistant Rubber Jacket • Smooth Jacket • UL/CSA Listed**600V, 90°C • Paper Tape Separator • Color Code: Black, White, Green, Red**

19217	50	15.2	10.1	4.6	Black	14 (41x30) BC	.048	1.22	.087	2.21	.603	15.32
	200	60.9	43.6	19.8								
19216	50	15.2	17.2	7.8	Black	12 (65x30) BC	.051	1.30	.102	2.59	.690	17.53
	200	60.9	61.8	28.1								

5-Conductor Rubber Jacket • Smooth Jacket • Style 4256**300V, 60°C • Paper Tape Separator • Color Code: Brown, Green, White, Black, Red**

8455*	250	76.2	12.0	5.4	Black	3-20 (26x34) TC	.018	.46	.031	.79	.280	7.11
	U-500	U-152.4	25.5	11.6								
	U-1000	U-304.8	50.0	22.7								
					2-18 (41x34) TC							

BC = Bare Copper • TC = Tinned Copper

*Not CSA recognized.

†Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.

††1000 ft. put-up one piece exact.