

3-, 4- and 5-Conductor

UL/CSA Type: SVT, SO

UL AWM Styles: 4097 and 4256

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm

3-Conductor SVT PVC Jacket • Shielded • Smooth Jacket • 22 AWG Drain Wire (7x30) • UL/CSA Listed**300V, 60°C Shielded • Beldfoil® Shield (100% Coverage) • International Color Code: Light Blue, Brown, Green/Yellow**

19401	250 †	76.2	12.3	5.6	Black	18 (42x34) BC	.018	.46	.043	1.09	.270	6.86
	1000 ††	304.8	49.0	22.3								

300V, 60°C Shielded • Duofoil® Shield (100% Coverage) • Braid (88% Coverage) • Internat'l Color Code: Light Blue, Brown, Green/Yellow


19403	250 †	76.2	17.8	8.1	Black	18 (42x34) BC	.018	.46	.038	.97	.307	7.80

4-Conductor Rubber Jacket • Smooth Jacket • Style 4097**300V, 60°C • Paper Tape Separator • Color Code: Black, White, Brown, Red**

8454*	100	30.5	5.8	2.6	Black	18 (41x34) TC	.018	.46	.036	.91	.265	6.73
	U-500	U-152.4	27.0	12.3								
	500	152.4	25.0	11.3								
	U-1000	U-304.8	52.0	23.6								
	1000	304.8	54.0	24.5								

4-Conductor SO Oil-Resistant Rubber Jacket • Smooth Jacket • UL/CSA Listed**600V, 90°C • Paper Tape Separator • Color Code: Black, White, Green, Red**

19217	50	15.2	10.1	4.6	Black	14 (41x30) BC	.048	1.22	.087	2.21	.603	15.32
	200	60.9	43.6	19.8								
19216	50	15.2	17.2	7.8	Black	12 (65x30) BC	.051	1.30	.102	2.59	.690	17.53
	200	60.9	61.8	28.1								

5-Conductor Rubber Jacket • Smooth Jacket • Style 4256**300V, 60°C • Paper Tape Separator • Color Code: Brown, Green, White, Black, Red**

8455*	250	76.2	12.0	5.4	Black	3-20 (26x34) TC	.018	.46	.031	.79	.280	7.11
	U-500	U-152.4	25.5	11.6								
	U-1000	U-304.8	50.0	22.7								
					2-18 (41x34) TC							

BC = Bare Copper • TC = Tinned Copper

*Not CSA recognized.

†Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.

††1000 ft. put-up one piece exact.